

Claims

WHAT IS CLAIMED IS:

5

1. A method of redirecting a request URL comprising:
receiving the request Uniform Resource Locator (URL) comprising data related to a
patterned URL and data related to a destination URL;
determining the patterned URL based on the data related to the patterned URL from the
10 request URL; and
generating a destination URL based on one or more of the patterned URL, the data related
to the destination URL from the request URL, and redirector configuration
information.

- 15 2. The method of claim 1, wherein generating a destination URL comprises:
parsing the patterned URL;
determining whether a character from the patterned URL indicates a pattern;
responsive to the character from the patterned URL indicating a pattern, interpreting the
pattern based on a data source type and a format specifier; and
20 responsive to the character from the patterned URL not indicating a pattern, copying the
character from the patterned URL to the destination URL.

3. The method of claim 2, wherein interpreting the pattern based on the format specifier
comprises responsive to the format specifier indicating a name of a service, looking up an
25 Hyper-Text Transfer Protocol (HTTP) address for the service and placing the address into
the destination URL.

4. The method of claim 2, wherein interpreting the pattern based on the format specifier comprises responsive to the format specifier indicating string data, copying the string data
30 into the destination URL.
5. The method of claim 2, wherein interpreting the pattern based on the format specifier comprises responsive to the format specifier indicating a language , rewriting the language as a corresponding culture and adding the culture to the destination URL.
5
6. The method of claim 2, wherein interpreting the pattern based on the format specifier comprises responsive to the format specifier indicating a language, rewriting the language as a corresponding culture and adding the culture to the destination URL if the language indicates other than English.
10
7. The method of claim 2, wherein interpreting the pattern based on the format specifier comprises responsive to the format specifier indicating a language, copying the language to the destination URL if the language indicates other than English.
- 15 8. The method of claim 2, wherein interpreting the pattern based on the format specifier comprises responsive to the format specifier indicating a culture, translating the culture to a Language Culture IDentifier (LCID) and placing the LCID into the destination URL.
9. The method of claim 2, wherein interpreting the pattern based on the format specifier
20 comprises responsive to the format specifier indicating a special string copy, copying a

following string to the destination URL only if a previous portion of the patterned URL caused data to be written to the destination URL.

10. The method of claim 2, wherein interpreting the pattern based on the data source type
25 comprises responsive to the data source type indicating that data is located in a path portion of the request URL, copying a path part from the request URL to the destination URL.
11. The method of claim 2, wherein interpreting the pattern based on the data source type
30 comprises responsive to the data source type indicating that data is located in a query string of the request URL, copying data from the query string of the request URL to the destination URL.
12. The method of claim 2, wherein interpreting the pattern based on the data source type
comprises responsive to the data source type indicating that data is located in a data
source identifier of the patterned URL, copying the data source identifier from the
5 patterned URL to the destination URL.
13. The method of claim 10, wherein the path portion is identified by a data source identifier
in the pattern.
- 10 14. The method of claim 11, wherein the query string is identified by a data source identifier
in the pattern.

15. A system comprising:
a processor; and
a memory coupled with and readable by the processor and having stored therein
instructions which, when executed by the processor, cause the processor to receive
5 a request Uniform Resource Locator (URL) comprising data related to a patterned
URL and data related to a destination URL, determine the patterned URL based on
the data related to the patterned URL from the request URL, and generate a
destination URL based on one or more of the patterned URL, the data related to
the destination URL from the request URL, and redirector configuration
10 information.
16. The system of claim 15, wherein generating a destination URL comprises:
parsing the patterned URL;
determining whether a character from the patterned URL indicates a pattern;
15 responsive to the character from the patterned URL indicating a pattern, interpreting the
pattern based on a data source type and a format specifier; and
responsive to the character from the patterned URL not indicating a pattern, copying the
character from the patterned URL to the destination URL.
- 20 17. The system of claim 16, wherein interpreting the pattern based on the format specifier
comprises responsive to the format specifier indicating a name of a service, looking up an
Hyper-Text Transfer Protocol (HTTP) address for the service and placing the address into
the destination URL.

- 25 18. The system of claim 16, wherein interpreting the pattern based on the format specifier
comprises responsive to the format specifier indicating string data, copying the string data
into the destination URL.
19. The system of claim 16, wherein interpreting the pattern based on the format specifier
30 comprises responsive to the format specifier indicating a language, rewriting the language
as a corresponding culture and adding the culture to the destination URL.
20. The system of claim 16, wherein interpreting the pattern based on the format specifier
comprises responsive to the format specifier indicating a language, rewriting the language
as a corresponding culture and adding the culture to the destination URL if the language
5 indicates other than English.
21. The system of claim 16, wherein interpreting the pattern based on the format specifier
comprises responsive to the format specifier indicating a language, copying the language
to the destination URL if the language indicates other than English.
- 10 22. The system of claim 16, wherein interpreting the pattern based on the format specifier
comprises responsive to the format specifier indicating a culture, translating the culture to
a corresponding Language Culture IDentifier (LCID) and placing the LCID into the
destination URL.
- 15 23. The system of claim 16, wherein interpreting the pattern based on the format specifier
comprises responsive to the format specifier indicating a special string copy, copying a

following string to the destination URL only if a previous portion of the patterned URL caused data to be written to the destination URL.

24. The system of claim 16, wherein interpreting the pattern based on the data source type comprises responsive to the data source type indicating that data is located in a path portion of the request URL, copying a path part from the request URL to the destination URL.
25. The system of claim 16, wherein interpreting the pattern based on the data source type comprises responsive to the data source type indicating that data is located in a query string of the request URL, copying data from the query string of the request URL to the destination URL.
26. The system of claim 16, wherein interpreting the pattern based on the data source type comprises responsive to the data source type indicating that data is located in a data source identifier of the patterned URL, copying the data source identifier from the patterned URL to the destination URL.
27. The system of claim 24, wherein the path part is identified by a data source identifier in the pattern.
28. The system of claim 25, wherein the query string is identified by a data source identifier in the pattern.

29. A computer-readable medium encoding a computer program of instructions for executing a computer process for redirecting a request URL, the computer process comprising: receiving the request Uniform Resource Locator (URL) comprising data related to a patterned URL and data related to a destination URL;
- 5 determining the patterned URL based on the data related to the patterned URL from the request URL; and
- generating a destination URL based on one or more of the patterned URL, the data related to the destination URL from the request URL, and redirector configuration information.
- 10
30. The computer-readable medium of claim 29, wherein generating a destination URL comprises:
- parsing the patterned URL;
- determining whether a character from the patterned URL indicates a pattern;
- 15 responsive to the character from the patterned URL indicating a pattern, interpreting the pattern based on a data source type and a format specifier; and
- responsive to the character from the patterned URL not indicating a pattern, copying the character from the patterned URL to the destination URL.
- 20 31. The computer-readable medium of claim 30, wherein interpreting the pattern based on the format specifier comprises responsive to the format specifier indicating a name of a service, looking up an Hyper-Text Transfer Protocol (HTTP) address for the service and placing the address into the destination URL.

- 25 32. The computer-readable medium of claim 30, wherein interpreting the pattern based on the
format specifier comprises responsive to the format specifier indicating string data,
copying the string data into the destination URL.
- 30 33. The computer-readable medium of claim 30, wherein interpreting the pattern based on the
format specifier comprises responsive to the format specifier indicating a language,
rewriting the language as a corresponding culture and adding the culture to the destination
URL.
- 35 34. The computer-readable medium of claim 30, wherein interpreting the pattern based on the
format specifier comprises responsive to the format specifier indicating a language,
rewriting the language as a corresponding culture and adding the culture to the destination
URL if the language indicates other than English.
35. The computer-readable medium of claim 30, wherein interpreting the pattern based on the
format specifier comprises responsive to the format specifier indicating a language,
copying the language to the destination URL is the language indicates other than English.
- 5 36. The computer-readable medium of claim 30, wherein interpreting the pattern based on the
format specifier comprises responsive to the format specifier indicating a culture,
translating the culture to a Language Culture IDentifier (LCID) and placing the LCID into
the destination URL.
- 10 37. The computer-readable medium of claim 30, interpreting the pattern based on the format
specifier comprises responsive to the format specifier indicating a special string copy,

copying a following string to the destination URL only if a previous portion of the patterned URL caused data to be written to the destination URL.

15

38. The computer-readable medium of claim 30, wherein interpreting the pattern based on the data source type comprises responsive to the data source type indicating that data is located in a path portion of the request URL, copying a path part from the request URL to the destination URL.

20

39. The computer-readable medium of claim 30, wherein interpreting the pattern based on the data source type comprises responsive to the data source type indicating that data is located in a query string of the request URL, copying data from the query string of the request URL to the destination URL.

25

40. The computer-readable medium of claim 30, wherein interpreting the pattern based on the data source type comprises responsive to the data source type indicating that data is located in a data source identifier of the patterned URL, copying the data source identifier from the patterned URL to the destination URL.

30

41. The computer-readable medium of claim 38, wherein the path part is identified by a data source identifier in the pattern.

35

42. The computer-readable medium of claim 39, wherein the query string is identified by a data source identifier in the pattern.